



# SePem<sup>®</sup> 150

## Device data

Dimensions (Ø × H)	54 × 114 mm (without magnet and aerial)
Weight	775 g
Material	stainless steel, polypropylene

## Certificates

Mark	CE
------	----

## Device elements

Interface	radio data
Memory	64 kB
Processor	microcontroller 16 bit
Operation	magnetic activation via reed contact

## Operating conditions

Operating temperature	-20 – 55 °C
Storage temperature	-20 – 70 °C
Humidity	100 % r.h.
Atmospheric pressure	900 – 1180 hPa
Protection rating	IP68
Permitted operating environments	outdoors submersible to 1 m
Non-permitted operating environments	<ul style="list-style-type: none"><li>• in liquids other than water</li><li>• in aggressive media</li><li>• in potentially explosive areas</li></ul>
Normal position of use	vertical

### Power supply

Power supply	lithium metal battery [1355-0017]
Lithium mass per battery	2.37 g
Operating time, typical	5 years (when using default settings)

### Data logging

Sampling rate	adjustable 1 s – 1 h
---------------	----------------------

### Data transmission

Transmission frequency	433 MHz
Communication	bi-directional radio data
Power	10 mW

### Additional data

Attachment option	magnetic at measuring point
Shipping instructions	UN 3091: lithium metal batteries contained in equipment or lithium metal batteries packed with equipment net weight of battery/batteries: 0.055 kg

### Assignment

For use with	SePem 01 Master safety rope
--------------	--------------------------------