



SePem[®] 352

Device data

Dimensions (H × Ø)	155 × 58 mm (without aerial)
Weight	900 g (without aerial)

Certificates

Certificate	<ul style="list-style-type: none">• CE• FCC
-------------	--

Features

Signal light	1 LED
Memory	128 kB
Processor	microcontroller 16 bit
Ports	<ul style="list-style-type: none">• TNC-port• 3-pin communication contact
Control	Reed switch for testing the radio connection

Operating conditions

Operating temperature	-20 – 55 °C
Storage temperature	-20 – 70 °C
Humidity	100 % r.h.
Atmospheric pressure	900 – 1180 hPa
Protection rating	IP68
Non-permitted operating environments	<ul style="list-style-type: none">• in liquids other than water• in aggressive media• in potentially explosive areas

Power supply

Power supply	lithium metal battery [1355-0022]
Lithium mass per cell	3.84 g
Net weight of batteries	96 g
Operating time, typical	12 years when using the default settings

Measurement data recording

Type	noise sensor
Sampling rate	adjustable 1 s – 1 h
Measuring range	0 – 3000

Data transmission

Communication	<ul style="list-style-type: none">● LoRaWAN®<ul style="list-style-type: none">○ standard: V1.0.4; LoRaWAN® Regional Parameters V1.0.3● cable
Frequency bands	LoRaWAN®: AS923-1, AU915, EU868, US915

Additional data

Attachment option	magnetically to the measuring location
Shipping instructions	contains: <ul style="list-style-type: none">● 1 lithium metal battery packed with equipment (UN 3091)● with 3.84 g lithium transport as per ADR class 9 and VA 970 part I IATA possible

Assignment

System components of	SePem system
----------------------	--------------

LoRaWAN® is a brand used under the LoRa Alliance® licence.

Subject to technical changes.