



SR-LD 200

Device data

Dimensions (W × D × H)	58 × 130 × 202 mm (2.28 × 5.12 × 7.96 in)
Weight	623 g (21.81 oz)

Certificates

Marking	CE
---------	----

Features

Display	LCD 1,8" 240 × 320 Pixel
Interface	<ul style="list-style-type: none">• charging socket• Bluetooth
Control	3 keys
Sensor	laser: <ul style="list-style-type: none">• measurement laser
Other features	<ul style="list-style-type: none">• audible alarm, can be deactivated• target laser• red dot sight

Operating conditions

Operating temperature	-20 – 50 °C (-4 – 122 °F)
Humidity	30 – 90% r.h., non-condensing
Atmospheric pressure	800 – 1,100 hPa
Protection rating	IP54
Non-permitted operating environments	in potentially explosive areas

Storage conditions

Storage temperature	-20 – 50 °C (-4 – 122 °F)
Humidity	30 – 90% r.h., non-condensing

Power supply

Power supply	lithium-ion battery (rechargeable) [9066-4003]
Net weight of batteries	<ul style="list-style-type: none"> weight per cell: 0.0475 kg (0.105 lb) total: $3 \times 0.0475 \text{ kg} = 0.143 \text{ kg}$ ($3 \times 0.105 \text{ lb} = 0.315 \text{ lb}$)
Operating time, typical	> 13 h
Battery power	36 Wh
Charging time	approx. 2.5 h
Charging temperature	10 – 45 °C (50 – 113 °F)
Charging voltage	12.6 V
Charging current	2 A
charging socket	USB-C (approved for supplied charger only)
Charger	charger SR-LD

Measurement laser

Laser class	1 (according to IEC 60825-1)
Feature	<ul style="list-style-type: none"> Infrared laser invisible distance for the safe detection of 100 % vol. CH₄ at 10 l/h: 50 m (164 ft)
Wavelength	1,653 nm
Measuring range	0 – 100,000 ppm·m methane
Resolution	5 ppm·m
Detection range	0.5 – 120 m (1.64 – 394 ft) (in ideal ambient conditions)
Response time	0.05 s

Target laser

Laser class	2 (according to IEC 60825-1)
Feature	colour: green
Wavelength	530 nm
Output power	≤ 1 mW

Additional data

Shipping instructions

contains:

- 1 lithium-ion battery included in equipment or packaged with equipment (UN 3481)
- 36 Wh

transport as per SV 188 ADR and VA 967, Part II IATA or VA 966, Part II IATA possible
